



Pigment pastes

## Estercolors

### Description

Pigment preparation based on unsaturated polyester resin

### Characteristics

- Styrene free

### Applications

Coating and mouldings, Shipping, Construction, Swimming pool, a.o.

### Packaging

- Metallic drum: 25 kg, 50 kg, 200 kg
- IBC 1 000 kg



# Product range

Product	Colour	Colour Index	Pigment %	Temperature resistance °C	Light Fastness*
013/3205	Yellow	PY 81	30	200	7 - 7
013/3402	Yellow	PY 83	20	200	7 - 6/7
201047	Yellow	PBR 24	43	>200	8 - 8
013/335.6536	Yellow	PY 42	35	200	8 - 8
013/4615	Orange	PO 36	30	180	8 - 7/8
013/4230	Red	PR 170	35	200	8 - 7/8
013/4300	Magenta	PR 122	25	>200	8 - 8
013/4550	Red	PR 101	60	>200	8 - 8
013/6600	Violet	PV 23	25	>200	7/8 - 7/8
013/6510	Blue	PB 29	60	>200	8 - 8
013/6200	Blue	PB 15:1	35	>200	8 - 8
013/6110	Blue	PB 15:3	30	>200	8 - 8
013/7100	Green	PG 7	35	>200	8 - 8
013/7550	Green	PG 17	65	>200	8 - 8
013/1101	White	PW 6	70	>200	8 - 8
013/0200	Black	PBI 7	20	>200	8 - 8
013/064.6106	Black	PBI 11	60	>200	8 - 8

\* The resistance properties are based on data from the pigment supplier. These values may vary according to the dosage level and the system used by the customer. It is the responsibility of the producer of the final article to verify light fastness, heat stability and other resistance properties in his system.