

**SIOEN** CHEMICALS

PIGMENT PASTES

# ALKYCOLORS

Colours make you smile!

<b>Description</b>	Pigment preparation White Spirit alkyd based
<b>Characteristics</b>	<ul style="list-style-type: none"><li>&gt; 2 types of solvent: White Spirit &lt;1% of aromatic or not</li><li>&gt; Indoor or outdoor application</li></ul>
<b>Applications</b>	<ul style="list-style-type: none"><li>&gt; Decorative paint</li></ul>
<b>Packaging</b>	<ul style="list-style-type: none"><li>&gt; Metallic drum: 25 kg, 50 kg, 200 kg</li></ul>



















## Why Sioen Chemicals is your ideal partner:

- > More than 50 Years of Industry Know-How
- > Standard and Taylor Made Customer Solutions
- > Extensive Pigment Portfolio Knowledge in respect to Cost, Performance and System Compatibility
- > Wide Range of Base Systems in Support to Sustainable Formulation Development
- > State-of-the-Art Production and Highly Qualified Operators
- > Environment, Health & Safety as Priority Number One
- > Strong Customer Focus and Proven Flexibility
- > Extensive Lab and R&D facilities
- > A Dedicated Team at Your Service
- > Part of a Solid Group Sioen Industries n.v.

GENERAL INFORMATION

WHY SIOEN CHEMICALS ?

Rijksweg 15 • 2880 Bornem • Belgium •  
tel +32 3 890 64 00 • fax +32 3 899 26 03 •  
emb@sioen.be • www.sioenchemicals.com

Product	Colour index	Pigment %	Temperature resistance* °C	Light fastness* FULL SHADE REDUCTION
 YELLOW 90067	PY 3	31	140	7 - 6
 YELLOW 90074	PY 73	27	140	7 - 5
 YELLOW 90225	PY 74	33	120	7/8 - 6/7
 YELLOW 90110	PY 65	40	140	7/8 - 6/7
 OXIDE YELLOW 90071	PY 42	60	200	8 - 8
 RED 90224	PR 112	29	180	7/8 - 6/7
 RED 90065	PR 3	29	180	7/8 - 5
 RED 90082	PR 48:4	19	*	7 - 5
 PINK 90248	PR 122	25	200	7/8 - 7/8
 OXIDE RED 90096	PR 101	66	>200	8 - 8
 VIOLET 90069	PV 23	25	>200	7/8 - 7/8
 BLUE 90226	PB 15:1	30	>200	7/8 - 7/8
 BLUE 90158	PB 15:2	25	>200	8 - 8
 BLUE 90256	PB 15:3	22	200	8 - 8
 GREEN 90072	PG 7	25	200	8 - 8
 WHITE 90241	PW 6	71	>200	8 - 8
 BLACK 90068	PBL 7	20	>200	8 - 8
 BLACK 90279	PBL 7	17	>200	8 - 8

\* The resistance properties are based on data from the pigment supplier. These values may vary according to the dosage level and the system used by the customer. It is the responsibility of the producer of the final article to verify light fastness, heat stability and other resistance properties in his system.

State-of-the-art production plants



Spirit of innovation



A team of professionals



**Colours** make you smile!